



## 4100 DATA SHEET



**THE EXPERIENCE**  
"FEEL THE FUTURE"

## Specifications

### General Information

The Q2 Energy Spa was created to realign, balance and enhance the bio energetic levels in water that is then used by the cells of all living things.

Designed and manufactured in Australia it leads the world in non invasive energetic hydro-therapy technology.

The model #4100, is our latest achievement, providing increased functionality through computer controlled circuitry.

This circuitry provides custom self adjustment, by automatically selecting the correct energy output for your water conditions. Other innovative features include self protection and self system diagnostics with a numerical action coded display, and a built in timer which will turn off the unit when the session time is up. These are but a few of the features of the 4100 to make it a very powerful tool for the professional user.

Best of all, this model comes with Not 1 but 2 Orb's, making it easier to use in a practice or relaxation clinic, giving you a backup unit to use while the other Orb is being cleaned, "no downtime". Designed to meet the International Electrical Equipment Isolation Safety Standards, IEC60601.1 with consideration to the international wiring rules with variations to suit Europe, USA, Canada and Australia.

The model #4100 power supply is double insulated, designed & built to comply with CE mark & UL requirements.

### Improved Clarity

Improvement to the circuitry and components for this model now produce a much cleaner source of power to the Orb which means better quality for you. As an added benefit this prolongs the life of your consumables.

### DVD Multimedia Presentation

The Q2 Energy Spa comes packaged with a multimedia presentation. This presentation contains live video coverage of events and best of all, it contains video footage of "How to Use" the Q2 Energy Spa and maintain the unit yourself.

### Your Model 4100 Energy Spa

- Innovative Q2 Orb x 2
- 20 Positive Ring & Track Sets
- Connection Cable
- Spare Fuses
  - 2 x 4Amps, 250V (F4AL250V)
  - 2 x 2Amps, 250V (F2AL250V)
- User Guide
- Quick Reference Guide
- Multimedia DVD Presentation
- Carry Bag
- Warranty Information & Card
- A5 Information Booklet
- Q - The Experience Limited Edition Pen

### Technical Information

Hardware upgradable  
Flash bios (software ungradable)  
Optimal level selection  
(auto adjusts to water quality)  
Automated system diagnostics  
Built in self protection & safety cutout  
Built in timer  
Improved Bio-Energy Enhancement  
Improved Electrical Signal Clarity  
Built to International Electrical Safety  
Isolation Standards IEC60601.1  
Compliance to CE Mark

**CLASS II Equipment**, Type B Applied Part  
Safety extra low voltage isolating DC Power Supply.

**Input:** 100 to 120Vac 50/60Hz, 95W or  
200 to 240Vac 50/60Hz, 95W  
As indicated on the power supply.

**Output:** Isolated, Rectified and Filtered,  
28Vdc, 3Amps.

**Dimensions:** 190x135x103mm

**Weight:** 2.8Kg (6.2 lbs)



**Model 4100**  
including 2 Orbs

### Australian Head Office

Q-Tech Laboratories P/L  
Gate 1 / 371 Taylor St.  
Toowoomba Qld 4350  
Ph: 07 4633 6600 Fax: 07 4633 6601  
Email: info@q2.com.au

**07 4633 6600**  
**www.q2.com.au**